

96-D Allen Boulevard Farmingdale, New York 11735-5626 USA Tel. +1 (631) 293-8944 Fax +1 (631) 293-8956 e-mail: testing@govmark.com

Page 1

Received: 04/26/2018 | Completed: 05/09/2018 | Letter: A2 | RV | P.O.#: Test Report #: 3-25811-2-Client's Style: Just. Content: 98% Post-Consumer Recycled Polyester, 2% Polyester. Finish: None. Weight: 317 g/lm. Color #: Identification 60120. Product End Use: Upholstery. Tested For: Bente Ellingsoe, Quality Department Key Test: ASTM D 4034/ACT 150 Gabriel A/S Hjulmagervej 55 Tel: 011-45-9630-3100 Ext: DK-9000 Aalborg, Denmark Fax: 011-45-9811-6125

Test Category: Seam Slippage

Specifier: ACT

LE 2015; V 08/15 PC: 8H

dl/SM

NTR 6/16

TEST PERFORMED: ASTM D 4034 - Standard Test Method for Resistance to Yarn Slippage at the Sewn Seam in Woven Upholstery Fabrics - Plain, Tufted, or Flocked --

As cited by the ACT Voluntary Performance Guidelines (January 2015)

PRODUCT CATEGORY: Upholstery

ACCEPTANCE CRITERIA: 25 lbf minimum average for warp and weft

SEAM CONSTRUCTION:

Seam Allowance: 0.5"

Seam Type: 301 Lockstitch

Thread Type:

100% Nylon Bonded Monocord;

Needle Thread size 8/Bobbin Thread Size 5

Needle:

Size 22 Ball Point

Stitches/Inch: 7 ± 0.5

RESULTS: Specimen results reported to the nearest 0.5 lb force (lbf)

Average reported to the nearest 0.5 lb force (lbf)

	Specimen	#	(lbf)	
Warp Yarn Slippage:	1		69.5	ss
(seamed in warp direction)	2		83.0	SS
	3		53.0	SS
	4		78.0	SS
	5		84.0	SS
		Avg:	73.5	
Weft Yarn Slippage:	6		105.0	ŞB
(seamed in weft direction)	7		104.5	ŞB
	8		92.5	SB
	9		99.0	SB
	10		91.5	SB
		Avg:	98.5	

ABBREVIATIONS WHICH MAY BE USED:

SS = Seam Slippage

SB = Seam break before 1/4" slippage

FB = Fabric break before 1/4" slippage

FBS = Fabric break at Seam before 1/4" slippage

(Page 1 of 2)



96-D Allen Boulevard Farmingdale, New York 11735-5626 USA Tel. +1 (631) 293-8944 Fax +1 (631) 293-8956 e-mail: testing@govmark.com

Page 2

Received:04/	26/2018 Completed: 05/09/2018	Letter: A2	RV	P.O.#:	Test Report #:	3-25811-2-
Client's Identificatio	Style: Just. Content: 98% Post- on 60120. Product End Use: Upho		ycled Po	lyester, 2% Polyester	: Finish: None. Weight: 317 g	g/lm. Color #:
Tested For:	Bente Ellingsoe, Quality Dep Gabriel A/S	partment		Key Test	: ASTM D 4034/ACT	150
	Hjulmagervej 55 DK-9000 Aalborg, Denmark				011-45-9630-3100 E 011-45-9811-6125	Ext:

REMARKS: None.

CONCLUSION: Based on the above Results and Acceptance Criteria, the item tested:

[x] Complies; [] Does not comply

CERTIFICATION: I certify that the above results were obtained after testing specimens in accordance with the procedures and equipment specified above.

AUTHORIZED SIGNATURE

Phyllis Pettit

GOVMARK

/ac

MAY 2 2 2018

(Page 2 of 2)