

Confidential Report

Our Ref: 23/59121L/11/21





Wira House, West Park Ring Road, Leeds, LS16 6QL, UK. Telephone: +44 (0) 113 259 1999

Email: info@bttg.co.uk

: www.bttg.co.uk

Date: 4 January 2022

Our Ref: 23/59121L/11/21

Your Ref: ---

Page: 1 of 4

Client: Gabriel A/S

Hjulmagerve 55 DK-900 Aalborg Denmark

Job Title: Fire Test on One Fabric Sample

Clients Order Ref: 0011572343

Date of Receipt: 24 November 2021

Date Test Started: 23 December 2021

Description of Sample: One sample of fabric, which was referenced by the client as;

Swing/Light Grey, stated to be: 54% WO/44% PES/2% PA

Work Requested: We were asked to test the received sample to the following standard:

BS EN 1021:Part 1:2014 - Ignitability of Upholstered Furniture



subcontracted test, UKAS accredited

** subcontracted test, EN ISO/IEC 17025 accredited

*** not UKAS accredited

Note: This report relates only to the samples submitted and as described in the report.



Wira House, West Park Ring Road, Leeds, LS16 6QL, UK.

Telephone: +44 (0) 113 259 1999

Email: <u>info@bttg.co.uk</u> : <u>www.bttg.co.uk</u>

Date: 4 January 2022

Our Ref: 23/59121L/11/21 Your Ref: ---

Page: 2 of 4

Client: Gabriel A/S

FIRE TEST ACCORDING TO BS EN 1021-1:2014

Assessment of the ignitability of upholstered furniture. Part I. Ignition Source 0: Smouldering cigarette

Pre-Treatment

The material received no pre-treatment as the fabric is stated not to be FR treated.

Conditioning

The sample was conditioned for at least 16 hours at a temperature of $23\pm2^{\circ}$ C and relative humidity of $50\pm5\%$.

The sample was tested in a room of volume 25m³ and 45°C.

Procedure

The test was carried out in accordance with BS EN 1021-1:2014. The sponsor sampled the material and the specimens were cut from the sample received to the dimensions set out in the standard.

The sample was tested over non-fire retardant polyurethane foam with a density of approximately 20-22 kg/m³.

Tests were made using ignition source 0.

Requirements

The specimens shall not:-

Smouldering Criteria

- a) display escalating combustion requiring active extinction.
- b) smoulder or burn until it is essentially consumed within the test duration.
- c) smoulder or burn to the extremities of the specimen, or through the full thickness, within the duration of the test.
- d) smoulder for more than one hour.
- e) on final examination, show evidence of progressive smouldering.





Wira House, West Park Ring Road, Leeds, LS16 6QL, UK.

Telephone: +44 (0) 113 259 1999

Email: <u>info@bttg.co.uk</u> : <u>www.bttg.co.uk</u>

Date: 4 January 2022

Our Ref: 23/59121L/11/21 Your Ref: ---

Page: 3 of 4

Client: Gabriel A/S

Requirements (continued)

Flaming Criteria

a) show evidence of flaming initiated by a smouldering source.

Results

Smouldering criteria	Specimen No.		
	1	2	3 ¹
Unsafe escalating combustion	No	No	No
Testing assembly consumed	No	No	No
Smoulders to extremities/full thickness	No	No	No
Smoulders more than 1 hour	No	No	No
In final examination, presence of progressive	No	No	No
smouldering			

Flaming criteria	1	2	31
Occurrence of flames	No	No	No
Specimen Result Ignition (I) / Non Ignition (NI)	NI	NI	NI

Any "Yes" in smouldering or flaming criteria means Ignition

Cigarette Test Result PASS

Note

The test results relate only to the ignitability of the combination of materials under the particular conditions of test; they are not intended as a means of assessing the full potential fire hazard of the materials in use.





Wira House, West Park Ring Road, Leeds, LS16 6QL, UK.

Telephone: +44 (0) 113 259 1999

Email: <u>info@bttg.co.uk</u> : <u>www.bttg.co.uk</u>

Date: 4 January 2022

Our Ref: 23/59121L/11/21

Your Ref: ---

Page: 4 of 4

Client: Gabriel A/S

Comment

An NI designation indicates the sample meets the performance requirements of BS EN 1021-1.

An estimation of uncertainty of measurement has been taken into account when making a judgment to any pass/fail criteria. Under our Policy we have used a non-binary decision rule.

See our Decision rules Policy (http://www.bttg.co.uk/decision-rules-policy) for further information.

The overall uncertainty budget for BS EN 1021:Part 1:2014 is as follows:-

Timings: ±2 seconds.

Reported by:.....

B Bland

Technical Customer Service Officer

Enquiries concerning this report should be addressed to Customer Services.

Countersigned By:

P Doherty

Manager

