

Page 1

Received: 11/1	6/2018 Completed: 11/21/2018	Letter: F	BG	P.O.#:	Test Report #:	3-2	9638-0-
Client's Style: Fame. Content: 95% Wools of New Zealand / 5% Polyamide. Weight: 630 g/lm. Color: 61136 Beige. Product End Use: Upholstery.							
Tested For: Bente Ellingsoe, Quality Department Key Test: CA TB 117-2013 (Section 1-Cover 2					235		
(	Gabriel A/S			]	Fabric) /ACT		
l I	Hjulmagervej 55			Tel: (	011-45-9630-3100	Ext:	
I	OK-9000 Aalborg, Denmark			Fax: (	011-45-9811-6125		

Test Category: Cigarette Ignition

Specifier: ACT

LE 2015; V 08/15

NTR 9/15

Product Category: Upholstery

PC: 24H

dl/SM

TEST PERFORMED: California Technical Bulletin 117-2013 - Requirements, Test Procedure and Apparatus for Testing the Smolder Resistance of Materials Used in Upholstered Furniture (June 2013 Version; V 1/18)

Section 1, Cover Fabric Test (Upholstery cover material is the outermost layer of fabric or related material used to enclose the main support system or upholstery materials, or both, used in the furniture item.) --

As cited by the ACT Voluntary Performance Guidelines (January 2015)

REFERENCE: ASTM E1353-08ae1

IGNITION SOURCE: SRM 1196 Cigarette

SPECIMEN TEST COMPOSITE:

Upholstery Cover Material: As described in "Client's Identification".

Standard Substrate Material: Non FR polyurethane foam, density 1.8 ± 0.05 lb/ft3

BRIEF DESCRIPTION OF TEST: Miniature cushions are prepared using the client's cover fabric over the standard filling material. The vertical or back cushions measure  $8" \times 8" \times 2"$ . The horizontal or seat cushions measure  $8" \times 5" \times 2"$ .

A lighted cigarette is placed in the crevice formed by the vertical cushion and the horizontal cushion.

The test is terminated at 45 minutes if smoldering is no longer observed.

Test measurements and observations are recorded.

-- See Page 3 for "Results" and "Conclusion" --

(Page 1 of 4)



Page 2

Received: 11/16/20	18 Completed: 11/21/2018	Letter: F	BG	P.O.#:	Test Report #:	3-2	29638-0-
Client's Styll Identification Use	e: Fame. Content: 95% Wo : Upholstery.	ols of New Zeala	nd / 5	% Polyamide. Weight	: 630 g/lm. Color: 61136	Beige. Produ	ct End
	e Ellingsoe, Quality Dep el A/S	artment		Key Test:	CA TB 117-2013 (Secti Fabric) /ACT	ion 1-Cover	235
Hjuln	nagervej 55 000 Aalborg, Denmark				011-45-9630-3100 011-45-9811-6125	Ext:	

PASS/FAIL/REPEAT CRITERIA: A material is considered to pass or fail based on the following criteria:

- 1. A single mock-up test specimen fails to meet the requirements of this test procedure if any of the following criteria occurs:
  - a) The mock-up test specimen continues to smolder after the 45 minute test duration;
  - b) A vertical char length (measured as specified in step 11.9 of ASTM E1353-08ael) of more than 1.8 inches (45 mm) develops on the cover fabric.
  - c) The mock-up test specimen transitions to open flaming.
- 2. The cover fabric passes the test if three initial mock-up specimens pass the test, i.e., the cigarettes burn their entire length and the mock-ups are no longer smoldering.
- 3. If more than one initial specimen fails, the cover fabric fails the test.
- 4. If any one of the three initial specimens fails, repeat the test on additional three specimens.
- 5. If all three additional specimens pass the test, the cover fabric passes the test. If any one of the additional three specimens fails, the cover fabric fails the test.

DISCUSSION: The current version of California Technical Bulletin 117-2013 has no provision to recognize cigarettes that self-extinguish prior to burning their entire length. However, ASTM E 1353 does recognize this phenomenon.

The SGS Govmark report evaluates replacement cigarettes as follows:

If a cigarette self-extinguishes (SE) before burning its entire length, a new cigarette is placed into the test. If the new (replacement) cigarette self-extinguishes or burns its entire length, the result for that specimen will then be evaluated as if the cigarette burned its entire length when assigning the "Passing/Failure" conclusion.



Page 3

Received: 11/16/2018	Completed: 11/21/	2018 Letter: F	BG <b>P.O.</b> #:	Te	st Report #:	3-296	38-0-
Client's Style: Identification Use: U		6 Wools of New Zeala	and / 5% Polyamide.	Weight: 630 g/lm.	Color: 61136 B	eige. Product I	Ind
Tested For: <b>Bente E</b> Gabriel A Hjulmag DK-9000	A/S	·	Ke	y Test: CA TB 1 Fabric) // Tel: 011-45-9 Fax: 011-45-9	ACT 630-3100	n 1-Cover Ext:	235
RESULTS:					·		
	Specimen #	Char Length (inches)	SE (yes/no) 	SB45 (yes/no)	TOF (yes/no)		
Initial:	1 2 3	0.3 0.3 0.3	No No No	No No No	No No No		
Replacement: (If needed)	1 2 3						
Repeat Tests: (If needed)	1 2 3						
EXPLANATION:							
Initial:	These are the draw a test co	first 3 cigarett	es where the res	sults could be	e sufficient	to	
Replacement:		initial cigarett test is conducte			rning their o	complete	
Repeat Test:	Depending on to draw a cond	che initial or reclusion.	placement result	ts, 3 repeat	tests might :	be required	
CODES USED:							
SB45 = Smolder TOF = Transit MNR = Measure transit EC = Escalat	r beyond 45 min tions to open f ement not recon tioned to open ting smoldering	laming ded as smolderin	ng exceeded 45 m.	inutes or spe	cimen		
CONCLUSION: The above resuindicate:	ults reported :	For the initial a	und / or replace	ment cigarett	es are suffi	cient to	
[x] Passing	g; [] Failure	e; [ ] Repeat tes	st on 3 addition	al specimens			
The results at	fter conducting	g the repeat test	s indicate:				
[ ] Passinq	g; [ ] Failure	(Page 3	of 4)				



Page 4

Received:11/16	5/2018 Completed: 11/21/2018	Letter: F	ВG	P.O.#:	Test Report #:	3-29638-0-	
Client's Style: Fame. Content: 95% Wools of New Zealand / 5% Polyamide. Weight: 630 g/lm. Color: 61136 Beige. Product End Use: Upholstery.							
Tested For: Bente Ellingsoe, Quality Department Gabriel A/S Hjulmagervej 55				Key Test: CA TB 117-2013 (Section 1-Cover 235 Fabric) /ACT Tel: 011-45-9630-3100 Ext:			
	K-9000 Aalborg, Denmark				5-9811-6125		

REMARKS: None.

CERTIFICATION: I certify that the above results were obtained after testing specimens in accordance with the procedures and equipment specified above.

AUTHORIZED SIGNATURE

SGS GOVMARK

/gb /pm

Phyllis Pettit

JAN 0 7 2019

(Page 4 of 4)